

## **RESIN INFORMATION SHEET**

Product Name	TSKgel® DEAE-5PW (Weak anion exchange chromatography resin)		
Part Numbers	43381 TSKgel DEAE-5PW (20), 25 mL		25 mL
	14710	TSKgel DEAE-5PW (20),	
	14711 TSKgel DEAE-5PW (20), 1 L		
	18436 TSKgel DEAE-5PW (20), 5 L		5 L
	43281	TSKgel DEAE-5PW (30), 25m L	
	14712	TSKgel DEAE-5PW (30), 250 mL	
	14713	TSKgel DEAE-5PW (30), 1 L	
	18370	TSKgel DEAE-5PW (30), 5 L	
Product Description	TSKgel is a methacrylic polymer with very high mechanical and chemical stability.  TSKgel DEAE-5PW chromatographic resin is designed for ion exchange chromatography. This chromatographic mode separates molecules on the basis of ionic interactions between the sample and the resin. The separation is usually accomplished in buffered aqueous solution with a gradient of increasing ionic strength. Alternatively, pH adjustment may be used for control of elution.		
Operating	Packing pressure		Typically 1 MPa
Conditions	Shipping solvent		20 % (v/v) ethanol
	Shipping formulation		72 % (v/v) slurry in shipping solvent (*)
	Pressure limiting factor		Depend on column hardware (typically 2 MPa)
	Operating linear flowrate		Typically 60 - 1200 cm/hour (depend on particle size)
	Long term storage conditions		20 % (v/v) ethanol
	Cleaning in place / sanitization		0.1 - 0.5 mol/L NaOH or 0.1 mol/L HCl
Specifications	Particle size distribution		15 - 25 μm for (20)-grade
	(Min. 70 % within range)		20 - 40 μm for (30)-grade
	Ion exchange capacity		0.05 - 0.11 eq/L
	Protein adsorption capacity (of BSA)		25 - 45 g/L for (20)-grade 20 - 40 g/L for (30)-grade
	Bacterial count		Max. 100 CFU/mL
	Endotoxin concentration		Max. 10.0 EU/mL
	Eluable matt	er	Max. 0.2 % (for dry gel)
	Foreign subst	cance (colored particle)	Unobserved
Address			
Additional	Appearance		White resin slurry which settles upon standing
Information	Mean pore diameter (base resin)		100 nm (*)

Lot-specific data are included in the Certificate of Analysis (COA) shipped with the product. For detailed test procedures please refer to the appropriate Regulatory Support File.

To actuated test procedures prease refer to the appropriate regulatory support river

(\*) The value is for reference only, not guaranteed.