

RESIN INFORMATION SHEET

Product Name	TOYOPEARL [®] MX-Trp-650M (A multimodal cationic and hydrophobic resin for protein pu	
Part Numbers	22817	TOYOPEARL MX-Trp-650M, 25 mL
	22818	TOYOPEARL MX-Trp-650M, 100 mL
	22819	TOYOPEARL MX-Trp-650M, 1 L
	22820	TOYOPEARL MX-Trp-650M, 5 L

Product Description	TOYOPEARL chromatographic resins are based on a rigid methacrylic polymer, resulting in high mechanical and chemical stability. Resins are available as non-functionalized "HW" series resins for size exclusion separations, and derivatized with surface chemistries for alternative modes of chromatography such as ion exchange, hydrophobic interaction or affinity separations.			
	TOYOPEARL MX-Trp-650M chromatographic resin is designed for mixed-mode separations. This chromatographic mode separates molecules on the basis of ionic and hydrophobic interactions between the sample and the resin. The separation is usually accomplished in buffered aqueous solution with a gradient of increasing ionic strength or pH adjustment.			
Operating	Packing pressure	Typically 0.3 MPa		
Conditions	Shipping solvent	20 % (v/v) ethanol		
	Shipping formulation	72 % (v/v) slurry in shipping solvent (*)		
	Pressure limiting factor	Depend on column hardware (typically 0.7 MPa)		
	Operating linear flowrate	Typically 10 - 600 cm/hour		
	Long-term storage conditions	20 % (v/v) ethanol (in a non-UV light transmitting opaque container)		
	Cleaning-in-place/Sanitization	0.1 - 0.5 mol/L NaOH or 0.1 mol/L HCl		
Specifications	Particle size distribution (min. 80 % within range)	50 - 100 μm		
	lon exchange capacity	0.08 - 0.15 eq/L		
	Protein adsorption capacity (of γ -globulin)	Min. 75 g/L		
	Bacterial count	Max. 100 CFU/mL		
	Endotoxin concentration	Max. 10.0 EU/mL		
	Eluable matter	Max. 0.2 % (for dry gel)		
	Foreign substance (colored particle)	Max. 6		
Additional	Appearance	White resin slurry which settles upon standing		
Information	Mean pore diameter (base resin)	100 nm (*)		
		(*) The value is for reference only, not guaranteed.		

Lot-specific data are included in the Certificate of Analysis (COA) shipped with the product. For detailed test procedures please refer to the appropriate Regulatory Support File.